

LUMINAIRE SCHEDULE

TYPE	MOUNTING	DESCRIPTION	MANUFACTURER CATALOG #	LIGHT SOURCE	POWER SUPPLY	VOLTS	INPUT WATTS
EX1	WALL	SURFACE MOUNTED EXIT SIGN; 5/8" DIE CAST ALUMINUM; FINISH (BRUSHED ALUMINUM, BLACK, OR WHITE) AS SELECTED BY ARCHITECT. INTEGRAL PHOTOLUMINESCENT PANEL CONTINUOUSLY CHARGED BY THE INTEGRAL LEDS UNDER NORMAL POWER CONDITIONS.	EVENLITE: AUR-1-BODY COLOR-1B	LED	INTEGRAL	120V	2W
EX2	CEILING	SIMILAR TO TYPE EX1 EXCEPT CEILING MOUNTED.	EVENLITE: AUR-1-BODY COLOR-CN	LED	INTEGRAL	120V	2W
EX3	GATE	NON-POWERED PHOTOLUMINESCENT GATE MOUNTED EXIT SIGN WITH POLYCARBONATE SHIELD.	EVENLITE: LUC-G-1-FRAME FINISH-U-LS	N/A	N/A	N/A	N/A
AA1	RECESSED	RECESSED LED 4" SQUARE APERTURE DOWNLIGHT WALLWASHER WITH NOMINAL 7" DEEP HOUSING; WITH SEMI SPECULAR SELF FLANGED REFLECTOR; 2000 LUMEN OUTPUT; 3000K CCT LEDS; DMX DIMMING DRIVER.	GOTHAM: EVO-SQLW-30/20-4AR-LSS-MVOLT-EDXB	LED 3000K CCT 85 CRI 2000 NOMINAL LUMENS	INTEGRAL ELECTRONIC DMX DIMMING	UNV	24W
AA2	RECESSED	SIMILAR TO TYPE AA1 EXCEPT WITH 0-10V DIMMING POWER SUPPLY.	GOTHAM: EVO-SQLW-30/20-4AR-LSS-MVOLT-EDB	LED 3000K CCT 85 CRI 2000 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	UNV	24W
AA3	RECESSED	SIMILAR TO TYPE AA1 EXCEPT WITH 0-10V DIMMING POWER SUPPLY AND 1500 LUMEN OUTPUT.	GOTHAM: EVO-SQLW-30/15-4AR-LSS-MVOLT-EDB	LED 3000K CCT 85 CRI 1500 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	UNV	18W
AA4	RECESSED	SIMILAR TO TYPE AA1 EXCEPT WITH 1500 LUMEN OUTPUT.	GOTHAM: EVO-SQLW-30/15-4AR-LSS-MVOLT-EDXB	LED 3000K CCT 85 CRI 1500 NOMINAL LUMENS	INTEGRAL ELECTRONIC DMX DIMMING	UNV	18W
AB1	RECESSED	RECESSED LED STEPLIGHT WITH DIE FORMED GALVANIZED STEEL CONSTRUCTION HOUSING WITH DIE CAST ALUMINUM SHARP CUT OFF LOUVERED FACEPLATE WITH INTEGRAL JUNCTION BOX.	COLE LIGHTING: L158W-J-SCL-DIM(0-10V)	LED 3000K CCT	INTEGRAL ELECTRONIC 0-10V DIMMING	UNV	2W
AB2	RECESSED	SIMILAR TO TYPE AB1 EXCEPT WITH BLUE LEDS.	COLE LIGHTING: L158W-J-SCL-DIM(0-10v)-BLUE	LED BLUE	INTEGRAL ELECTRONIC 0-10V DIMMING	UNV	2W
AC1	RECESSED	RECESSED LINEAR LED DOWNLIGHT WITH EXTRUDED ALUMINUM CONSTRUCTION HOUSING, FLAT ENDCAPS, AND 4" WIDE OPAL WHITE TRANSLUCENT DIFFUSER WITH 73% TRANSMISSION AND 99% DIFFUSION. DIE FORMED 20-GAUGE HIGH REFLECTANCE MATTE WHITE POWDER COAT REFLECTOR. 12" NOMINAL LENGTH. VERIFY CEILING TRIM HARDWARE WITH THE ARCHITECT.	FINELITE: HP-4 R-12'-B-830-F-120V-SC-CEI LING	LED 3000K CCT	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	60W
AC2	RECESSED	SIMILAR TO TYPE AC1 EXCEPT WITH 16' NOMINAL LENGTH.	FINELITE: HP-4 R-16'-B-830-F-120V-SC-CEI LING	LED 3000K CCT	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	80W
AC3	RECESSED	SIMILAR TO TYPE AC1 EXCEPT WITH 24' NOMINAL LENGTH.	FINELITE: HP-4 R-24'-B-830-F-120V-SC-CEI LING	LED 3000K CCT	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	120W
AD1	PENDANT	PENDANT MOUNTED LINEAR LED INDIRECT/DIRECT LUMINAIRE WITH EXTRUDED ALUMINUM CONSTRUCTION HOUSING, FLAT ENDCAPS, AND OPAL WHITE TRANSLUCENT DIFFUSER. 56% UPLIGHT AND 44% DOWNLIGHT DISTRIBUTION. 8" NOMINAL LENGTH. 2.25" W X 5.5" H X 8' LENGTH. VERIFY CEILING TRIM HARDWARE WITH THE ARCHITECT. VERIFY FINISH WITH THE ARCHITECT.	ALIGHT: AC12-8'-ILS-DLS-30-U-M-D-HE-S-FINISH-1-D-EC(AS NOTED)	LED 3000K CCT 813 LUMENS PER FOOT	INTEGRAL ELECTRONIC 0-10V DIMMING	UNV	76W
AE1	SURFACE	SURFACE WALL MOUNTED LED DOWNLIGHT SCONCE. DIE CAST ALUMINUM CONSTRUCTION WITH IES TYPE III OPTICAL DISTRIBUTION. WIDTH: 10.25"; HEIGHT: 3.1"; DEPTH: 7.7". FACTORY STANDARD FINISH TO BE DETERMINED BY THE ARCHITECT.	LIGMAN LIGHTING: UVK-30001-20W LED-T4-W30-FINISH-120/277V-F	3000K 80CRI LED 2251 LM	NON-DIMMING	277V	21W
AF1	SURFACE	WALL MOUNTED DECORATIVE SCONCE WITH ALUMINUM FINS AND OPAL WHITE DIFFUSER. 9" W X 4" NOMINAL HEIGHT X 4" DEEP. FINISH TO BE DETERMINED BY THE ARCHITECT.	BORDEN LIGHTING: 510-LED14-120-FINISH	LED 3000K CCT 1430 LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	14W
AG1	PENDANT	PENDANT MOUNTED LED STRIPLIGHT WITH HEAVY GAUGE COLD ROLLED STEEL HOUSING AND END CAPS. CONTOURED FROSTED ACRYLIC LENS WITH WIDE DISTRIBUTUION; 4' NOMINAL LENGTH, 3" WIDTH, 4" NOMINAL HEIGHT; FACTORY PAINTED AFTER FABRICATION WHITE FINISH.	METALUX: 4SNLED-LD5-50SL-LW-UNV -L830-CD-1-U AYC CHAIN SET IF REQUIRED	LED 3000K CCT 5200 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	46W
AG2	SURFACE	SIMILAR TO TYPE AG1 EXCEPT WITH 2' NOMINAL LENGTH.	METALUX: 2SNLED-LD5-23SL-LW-UNV -L830-CD-1-U	LED 3000K CCT 2400 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	21W
AH1	PENDANT	PENDANT MOUNTED LED LINEAR DOWNLIGHT WITH EXTRUDED ALUMINUM HOUSING AND MATTE PARABOLIC LOUVERS. 1 7/8" W X 3 1/8" H X 4' L. FINISH TO BE DETERMINED BY THE ARCHITECT.	LUMENWERK: SQUDD-MPL-NA-LED-80-75 0-30-UNV-4'-D1-1-53WAC3 6-FINISH	LED 3000K CCT 3000 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	32W
AJ1	SURFACE	SURFACE WALL MOUNTED LED LUMINAIRE WITH EXTRUDED ALUMINUM CONSTRUCTION HOUSING, FLAT END PLATES, ROUND TRANSLUCENT ACRYLIC DIFFUSER. 2 3/8" H X 3' D X 5' NOMINAL LENGTH. WHITE FINISH.	PRUDENTIAL: R1-LED30-MO-R5'-TMW-UN V-SUR-DM10-EBCP_G-PR UBIN	LED 3000K CCT 3500 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	35W
AJ2	SURFACE	SIMILAR TO TYPE AJ1 EXCEPT 6' NOMINAL LENGTH.	PRUDENTIAL: R1-LED30-MO-6'-TMW-UN V-SUR-DM10-EBCP_G-PRU BIN	LED 3000K CCT 4200 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	42W
AL1	SURFACE	SURFACE MOUNTED LED CYLINDER. EXTRUDED ALUMINUM CYLINDER WITH DIE CAST ALUMINUM BEZEL AND CANOPY. 40 DEGREE MEDIUM DISTRIBUTION. MATTE BLACK FINISH. SNOOT ACCESSORY. CLEAR POLYCARBONATE OPTICAL LENS. PROVIDE ALL CONTROL BOXES AND DMX DIMMING TRANSLATORS. 13" H X 4" DIAMETER.	LUMENPULSE: LACYS-A-SM-D-120-13-DL2 0-30K-CR80-M-DMX/RDM-SN-MBK-B-MBK CBX-DS-LID	LED 3000K CCT 2000 LUMENS	INTEGRAL ELECTRONIC DMX DIMMING	120V	18W
AL2	SURFACE	SIMILAR TO TYPE AL1 EXCEPT WITH WALLWASH DISTRIBUTION AND HALF SNOOT.	LUMENPULSE: LACYS-A-SM-D-120-13-DL2 0-30K-CR80-WW-DMX/RD M-HSN-MBK-B-MBK CBX-DS-LID	LED 3000K CCT 2000 LUMENS	INTEGRAL ELECTRONIC DMX DIMMING	120V	18W
AM1	PENDANT	PENDANT MOUNTED LED STRIPLIGHT WITH HEAVY GAUGE COLD ROLLED STEEL HOUSING AND END CAPS. CONTOURED FROSTED ACRYLIC LENS WITH NARROW DISTRIBUTUION; 4' NOMINAL LENGTH, 3" WIDTH, 4" NOMINAL HEIGHT; FACTORY PAINTED AFTER FABRICATION BLACK FINISH.	METALUX: 4SNLED-LD5-74HL-LN-UNV -L830-CD-1-U AYC CHAIN SET IF REQUIRED	LED 3000K CCT 7500 NOMINAL LUMENS	INTEGRAL ELECTRONIC 0-10V DIMMING	120V	62W
AN1	PENDANT	PENDANT MOUNTED LED DOWNLIGHT WITH ALUMINUM AND STEEL CONSTRUCTION HOUSING, POWDER COAT FINISH, RECESSED ALUMINUM REFLECTORS WITH 60" DISTRIBUTION. BLACK FINISH. 8" NOMINAL DIAMETER X 10" NOMINAL HEIGHT.	ETC LIGHTING: ARCP4R-4-3-60-B-H	LED 3000K CCT 90 CRI 5991 LUMENS	INTEGRAL ELECTRONIC DMX DIMMING	120V	100W



PERFORMING ARTS BUILDING

NOVATO UNIFIED
SCHOOL DISTRICT

ARCH PROJECT NO:	1700.02
DRAWN BY:	LN/TV
DRAWING SCALE:	AS NOTED
PTN:	65417-138

FEB 15, 2019

LUMINAIRE SCHEDULE

E-0.2